

IA24I

Red Long Decap Aqueous Ink

IA241 is an aqueous ink suitable for printing on porous media. Available in HP 45 inkjet cartridges and bulk containers, IA241 is well-suited for a variety of printing applications, especially marking on lumber and corrugated packaging materials. Its excellent decap time ensures low intervention. This ink is water fast with superior adhesion.

General Specifications

| Ink part number | IA241 | |
|-------------------------------|------------|---|
| Target substrates | Porous | |
| Ink vehicle | Water | |
| Colorant type | Pigment | |
| Drop volume (nominal) | 25 pL | Varies with application and temperature |
| Maximum firing frequency | 15 kHz | |
| Shelf life (single cartridge) | 12 months | |
| Dry time | <2 seconds | |
| Operating conditions | 10-40°C | |
| Storage conditions | 10-30°C | |
| Voltage | 10 V | |
| Pulse width | 2.2 μsec | |
| Head warming temperature | N/A | |
| Decap time | >1 hour | |

Inkjet Technology by





Red Long Decap Aqueous Ink

Cartridge Maintenance and Handling

- •Clean the cartridge with a lint free cloth and wipe along the length of the printhead.
- •If necessary, moisten the cloth first with water or denatured alcohol.

Cartridge Storage

•Remove cartridge from printer and replace clip if cartridge will not be used for 24 hours or more.

Disclaimer

WE DECLARE OUR LIABILITY TO BE THE PRICE OF THE CARTRIDGE. We are committed to a continuing program of product improvement. Thus, please be advised that specifications, performance, parameters and appearance of our products are subject to change without notice. The information (including performance parameters) provided about this ink is based on tests conducted under controlled conditions. Since conditions of actual use may differ and are beyond our control, use this ink at your own risk and test for suitability in the application. We only guarantee initial start-up of the cartridge prior to the use by date listed on the cartridge packaging. MSDS IS AVAILABLE UPON REQUEST.

